

DECLARATION OF PERFORMANCE

Page 1 of 2

No. 18/S031F

Edition 10

1. Unique identification code of product type:

EPS S 031 PRO LAMBDA SUPER
EPS EN 13163 T(1)-L(2)-W(2)-S_b(5)-P(5)-BS115-DS(N)2-DS(70,-)2-TR100

2. Intended use(s):

Thermal insulation in building industry.

3. Manufacturer:

Paneltech Sp. z o.o., 41-508 Chorzów, ul. Michałkowicka 24, Poland.

4. System(s) of assessment and verification of constancy of performance:

System 3

5. Harmonized standard:

EN 13163:2012+A1:2015

Notified Body (Bodies):

- Łukasiewicz Research Network - Warsaw Institute of Technology (Notified Body No. 1454)

6. Declared performance:

Table 1

| Essential characteristics | Performance | Declared level/class/limit/NPD ¹⁾ | Harmonized technical specification |
|---|---|--|------------------------------------|
| Thermal resistance | Thermal resistance R_D Thermal conductivity coefficient λ_D | See Table 2 0,031 [W/mK] | EN 13163: 2012+A1:2015 |
| | Thickness, d_N | T(1) (±1 mm) d_N (See Table 2) | |
| Reaction to fire | Reaction to fire | E | |
| Stability of reaction to fire as a function of heat, atmospheric conditions, ageing/degradation | Stability of performance ²⁾ | E | |
| Stability of thermal resistance as a function of heat, atmospheric conditions, ageing/degradation | Thermal resistance R_D ³⁾ Declared thermal conductivity coefficient λ_D ³⁾ | See Table 2 0,031 [W/mK] | |
| | Stability of performance | DS(70,-)2 | |
| Compression resistance | Compressive stress at 10% deformation | NPD | |
| Tensile/bending strength | Bending strength | BS115 (≥100 kPa) | |

DECLARATION OF PERFORMANCE

Page 2 of 2

No. 18/S031F

Edition 10

| Essential characteristics | Performance | Declared level/class/limit/NPD ¹⁾ | Harmonized technical specification |
|---|---|--|------------------------------------|
| Stability of compression strength as a function of ageing and degradation | Creep in compression | NPD | EN 13163: 2012+A1:2015 |
| | Freeze-thaw resistance | NPD | |
| | Long-term reduction of thickness | NPD | |
| Water permeability | Water absorption under long-term immersion | NPD | |
| | Water absorption under long-term diffusion | NPD | |
| Vapour permeability | Vapour transmission | NPD | |
| Impact sound insulation index (for floors) | Dynamic stiffness | NPD | |
| | Thickness, d_L | NPD | |
| | Compressibility, c | NPD | |
| Continuous burning as glowing | Continuous burning as glowing | NPD | |
| Release of hazardous substances to the environment | Release of hazardous substances ⁴⁾ | NPD | |

¹⁾ NPD (No Performance Determined) ²⁾ Performance of EPS for fire does not deteriorate over time ³⁾ Thermal conductivity coefficient and thermal resistance do not change over time ⁴⁾ European test methods are in preparation

Table 2 Statement of thermal resistance as a function of thickness

| | | | | | | | | | | | | | | | |
|---|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| Thickness, d_N [mm] | 10 | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 | 130 | 140 | 150 |
| Thermal resistance R_D [m ² K/W] | 0,30 | 0,60 | 0,95 | 1,25 | 1,60 | 1,90 | 2,25 | 2,55 | 2,90 | 3,20 | 3,50 | 3,85 | 4,15 | 4,50 | 4,80 |
| Thickness, d_N [mm] | 160 | 170 | 180 | 190 | 200 | 210 | 220 | 230 | 240 | 250 | 260 | 270 | 280 | 290 | 300 |
| Thermal resistance R_D [m ² K/W] | 5,15 | 5,45 | 5,80 | 6,10 | 6,45 | 6,75 | 7,05 | 7,40 | 7,70 | 8,05 | 8,35 | 8,70 | 9,00 | 9,35 | 9,65 |

Performance of the above product conforms to the set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the manufacturer, as above.

Signed on behalf of the manufacturer by:

PREZES ZARZĄDU

[Signature]
Name and position

Chorzów, 29.07.2024 r.