

DECLARATION OF PERFORMANCE

Page 1 of 2

No. 04A/S038_70F

Edition 10

1. Unique identification code of product type:

EPS 70 038 FACADE SUPER
EPS EN 13163 T(1)-L(2)-W(2)-S_b(5)-P(5)-BS115-CS(10)70-DS(N)2-DS(70,-)1-TR100

2. Intended use(s):

Thermal insulation in building industry.

3. Manufacturer:

Paneltech Sp. z o.o., 41-508 Chorzów, ul. Michałkowicka 24, Poland.

4. System(s) of assessment and verification of constancy of performance:

System 3

5. Harmonized standard:

EN 13163:2012+A1:2015

Notified Body (Bodies):

- Building Research Institute (ITB) (Notified Body No. 1488)
- Research and Development Centre of the Building Insulation Industry (Notified Body No. 1486)

6. Declared performance:

Table 1

Essential characteristics	Performance	Declared level/class/limit/NPD ¹⁾	Harmonized technical specification
Thermal resistance	Thermal resistance R_D Thermal conductivity coefficient λ_D	See Table 2 0,038 [W/mK]	EN 13163: 2012+A1:2015
	Thickness, d_N	T(1) (±1 mm) d_N (See Table 2)	
Reaction to fire	Reaction to fire	E	
Stability of reaction to fire as a function of heat, atmospheric conditions, ageing/degradation	Stability of performance ²⁾	E	
Stability of thermal resistance as a function of heat, atmospheric conditions, ageing/degradation	Thermal resistance R_D ³⁾ Declared thermal conductivity coefficient λ_D ³⁾	See Table 2 0,038 [W/mK]	
	Stability of performance	DS(70,-)1	
Compression resistance	Compressive stress at 10% deformation	CS(10)70 (≥70 kPa)	
Tensile/bending strength	Bending strength	BS115 (≥115 kPa)	

DECLARATION OF PERFORMANCE

Page 2 of 2

No. 04A/S038_70F

Edition 10

Essential characteristics	Performance	Declared level/class/limit/NPD ¹⁾	Harmonized technical specification
Stability of compression strength as a function of ageing and degradation	Creep in compression	NPD	EN 13163: 2012+A1:2015
	Freeze-thaw resistance	NPD	
	Long-term reduction of thickness	NPD	
Water permeability	Water absorption under long-term immersion	NPD	
	Water absorption under long-term diffusion	NPD	
Vapour permeability	Vapour transmission	NPD	
Impact sound insulation index (for floors)	Dynamic stiffness	NPD	
	Thickness, d_L	NPD	
	Compressibility, c	NPD	
Continuous burning as glowing	Continuous burning as glowing	NPD	
Release of hazardous substances to the environment	Release of hazardous substances ⁴⁾	NPD	

¹⁾ NPD (No Performance Determined) ²⁾ Performance of EPS for fire does not deteriorate over time ³⁾ Thermal conductivity coefficient and thermal resistance do not change over time ⁴⁾ European test methods are in preparation

Table 2 Statement of thermal resistance as a function of thickness

Thickness, d_N [mm]	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150
Thermal resistance R_D [m ² K/W]	0,25	0,50	0,75	1,05	1,30	1,55	1,80	2,10	2,35	2,60	2,85	3,15	3,40	3,65	3,90
Thickness, d_N [mm]	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300
Thermal resistance R_D [m ² K/W]	4,20	4,45	4,70	5,00	5,25	5,50	5,75	6,05	6,30	6,55	6,80	7,10	7,35	7,60	7,85

Performance of the above product conforms to the set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the manufacturer, as above.

Signed on behalf of the manufacturer by:

WICEPREZES ZARZADU

mgr inż. Marek Romański

(full name and position)

Chorzów, 03.08.2020 r.